



OZM-5 with camera



OZP-5 with camera



OZP-5 with tablet

First-class optics as well as strong illumination combined with a high level of flexibility and digital tools

Features

- Stereomicroscopes from the OZM and OZP range are now also available to you as a comprehensive digital solution for your live investigations. Optionally available with an mounted tablet or C-mount camera. Naturally, the appropriate C-mount adapter is included with the delivery
- The mounted KERN ODC 241 tablet-camera has been specially developed for simple, convenient and direct investigation of the sample on the screen. Ideally suited for school pupils and students in education or for demonstration purposes in the laboratory
- The mounted C-mount camera is available in different versions and can be used anywhere
- For detailed information on the individual components, see the relevant product description of the individual item
- A protective dust cover, eye cups, as well as multi-lingual user instructions are included in the scope of the delivery

Technical data

- Optical system: Greenough optics
- Brightness adjustable (separate)
- Light distribution: 100:0
- Diopter adjustment: Both-sided
- Net weight approx. 5,5 kg
- Eyepiece: HSWF 10×/ø 23 mm
- Stand: Pillar style
- Illumination: 3 W LED (incident + transmitted)

OZM-5

- Tube 45° inclined
- Magnification ratio: 6,4:1
- Interpupillary distance 52 – 76 mm
- Overall dimensions W×D×H 330×285×440 mm
- Field of view: ø 32,8 – 5,1 mm
- Objective: 0,7× – 4,5×

OZP-5

- Tube: 35° inclined
- Magnification ratio: 9,2:1
- Interpupillary distance 52 – 76 mm
- Overall dimensions W×D×H 330×285×470 mm
- Field of view: ø 38,3 – 4,2 mm
- Objective: 0,6× – 5,5×

Model

Standard configuration (camera)

KERN	Included camera	Resolution camera	Interface	Sensor	Details microscope, camera
OZM 544C825	ODC 825	5 MP	USB 2.0 (6,8 – 55 FPS)	CMOS 1/2,5"	KERN Optics catalogue Page 52, 85
OZM 544C832	ODC 832	5 MP	USB 3.0 (14,2 – 101,2 FPS)	CMOS 1/2,5"	KERN Optics catalogue Page 52, 85
OZP 558C825	ODC 825	5 MP	USB 2.0 (6,8 – 55 FPS)	CMOS 1/2,5"	KERN Optics catalogue Page 54, 85
OZP 558C832	ODC 832	5 MP	USB 3.0 (14,2 – 101,2 FPS)	CMOS 1/2,5"	KERN Optics catalogue Page 54, 85
OZP 558T241	ODC 241	5 MP	WiFi, USB 2.0, HDMI, SD (15 – 30 FPS)	CMOS 1/2,5"	KERN Optics catalogue Page 54, 89

360° rotatable microscope head	Fluorescence illumination for compound microscopes With 100 W mercury lamp and filter	Integrated scale In the eyepiece	Battery operation Ready for battery operation. The battery type is specified for each device.
Monocular Microscope For the inspection with one eye	Fluorescence illumination for compound microscopes With 3 W LED illumination and filter	SD card For data storage	Battery operation rechargeable Prepared for a rechargeable battery operation
Binocular Microscope For the inspection with both eyes	Phase contrast unit For a higher contrast	USB 2.0 interface For data transmission	Plug-in power supply 230V/50Hz in standard version for EU. On request GB, AUS or USA version.
Trinocular Microscope For the inspection with both eyes and the additional option for the connection of a camera	Darkfield condenser/unit For a higher contrast due to indirect illumination	USB 3.0 interface For data transmission	Integrated power supply unit Integrated in microscope. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.
Abbe Condenser With high numerical aperture for the concentration and the focusing of light	Polarising unit To polarise the light	WIFI data interface: For transmitting of the picture to a mobile display device	Package shipment The time required to manufacture the product internally is shown in days in the pictogram.
Halogen illumination For pictures bright and rich in contrast	Infinity system Infinity corrected optical system	HDMI digital camera For direct transmitting of the picture to a display device	Pallet shipment The time required to manufacture the product internally is shown in days in the pictogram.
LED illumination Cold, energy-saving and especially long-life illumination	Zoom magnification For stereomicroscopes	PC software To transfer the measurements from the device to a PC.	Automatic temperature compensation For measurements between 10 °C and 30 °C
Incident illumination For non-transparent objects	Auto-focus For automatic control of the focus level	Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989+A1:1999+A2:2013	
Transmitting illumination For transparent objects	Parallel optical system For stereomicroscopes, enables fatigue-proof working		
Fluorescence illumination For stereomicroscopes			

Abbreviations

C-Mount	Adapter for the connection of a camera to a trinocular microscope	SLR camera	Single-Lens Reflex camera
FPS	Frames per second	SWF	Super Wide Field (Field number at least \varnothing 23 mm for 10 \times eyepiece)
H(S)WF	High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)	W.D.	Working Distance
LWD	Long Working Distance	WF	Wide Field (Field number up to \varnothing 22 mm for 10 \times eyepiece)
N.A.	Numerical Aperture		