

Pocket Balances KERN TGC · TGD



Slim pocket balance with large stainless steel weighing plate and practical tare pan

Features

- High-resolution pocket balance with particularly rapid reaction and stabilisation time, which means that you can work extremely efficiently
- Particularly flat design
- **1** Cover made of shock proof plastic as protection against pressure and dust. Can also be used as a tare cup
- Stainless steel weighing plate, which makes cleaning easy and hygienic
- Ready for use: Batteries included, 2×CR2032, operating time up to 8,75 h. Integrated AUTO-OFF function after 4 minutes to preserve the batteries



Compact pocket carat balance for precision weighing of jewellery and precious stones

Features

- Simple and convenient 4-key operation
- Can be switched over from g to ct, gn, dwt, ozt, oz at the touch of a key
- Innovative touchscreen: Large touch-sensitive, backlit touch display with very good contrast for easy operation and convenient reading
- Hard case cover as protection against pressure and dust
- Stainless steel weighing plate, which makes cleaning easy and hygienic
- Weighing pan standard
- Powder scale with Grain division (gn), ideal for sport shooters, reloaders etc. for self-filling cartridge cases
- USB cable for power supply as standard
- Ready for use: Batteries included, 4×1.5 V AAA, operating time up to 150 h. Integrated AUTO-OFF function after 5 minutes to preserve the batteries
- **2** Delivered in single design packaging



STANDARD



OPTION



KERN	TGC 150-2	TGC 500-1	TGC 1K-3	TGD 50-3C
Weighing capacity [Max] g	150	500	1000	50 250 ct
Readability [d] g	0,01	0,1	1	0,001 0,005 ct
LCD display - backlit		yes		yes
LCD display - digit height		12 mm		20 mm
Dimensions of weighing plate W×D mm		81 mm		65 mm
Overall dimensions W×D×H		100×130×18 mm		96×150×64 mm
Net weight		200 g		250 g
Permissible ambient temperature		0 °C - 40 °C		5 °C - 35 °C
Price, excl. of VAT, ex works, €				
Option DAkkS Calibr. Certificate, €		963-127		963-127

Internal adjusting
Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)

Adjusting program CAL
For quick setting up of the balance's accuracy. External adjusting weight required

EasyTouch
Suitable for the connection, data transmission and control through PC or tablet

Memory
Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.

Alibi memory
Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.

KERN Universal Port (KUP)
allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WIFI, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort

RS-232 Data interface
To connect the balance to a printer, PC or network

RS-485 Data interface
To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible

USB Data interface
To connect the balance to a printer, PC or other peripherals

Bluetooth* Data interface
To transfer data from the balance to a printer, PC or other peripherals

WIFI Data interface
To transfer data from the balance to a printer, PC or other peripherals

Control outputs
(optocoupler, digital I/O)
To connect relays, signal lamps, valves, etc.

Analogue interface
to connect a suitable peripheral device for analogue processing of the measurements

Interface for second balance
For direct connection of a second balance

Network interface
For connecting the scale to an Ethernet network

KERN Communication Protocol (KCP)
It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems

GLP/ISO log intern
The balance displays weight, date and time, independent of a printer connection

GLP/ISO log Printer
With weight, date and time. Only with KERN printers.

Piece counting
Reference quantities selectable. Display can be switched from piece to weight

Recipe level A
The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out

Recipe level B
Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display

Totalising level A
The weights of similar items can be added together and the total can be printed out

Percentage determination
Determining the deviation in % from the target value (100 %)

Weighing units
Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details

Weighing with tolerance range (Checkweighing)
Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model

Hold function
(Animal weighing program)
When the weighing conditions are unstable, a stable weight is calculated as an average value

Protection against dust and water splashes IPxx
The type of protection is shown in the pictogram

Suspended weighing
Load support with hook on the underside of the balance

Battery operation
Ready for battery operation. The battery type is specified for each device

Rechargeable battery pack
Rechargeable set

Universal plug-in power supply
with universal input and optional input socket adapters for
A) EU, CH, GB
B) EU, CH, GB, US
C) EU, CH, GB, US, AUS

Plug-in power supply
230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available

Integrated power supply unit
Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request

Weighing principle Strain gauges
Electrical resistor on an elastic deforming body

Weighing principle Tuning fork
A resonating body is electromagnetically excited, causing it to oscillate

Weighing principle Electromagnetic force compensation
Coil inside a permanent magnet. For the most accurate weighings

Weighing principle Single cell technology
Advanced version of the force compensation principle with the highest level of precision

Conformity Assessment
The time required for conformity assessment is specified in the pictogram

DAkkS calibration possible (DKD)
The time required for DAkkS calibration is shown in days in the pictogram

Factory calibration (ISO)
The time required for Factory calibration is shown in days in the pictogram

Package shipment
The time required for internal shipping preparations is shown in days in the pictogram

Pallet shipment
The time required for internal shipping preparations is shown in days in the pictogram

* The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.